Date Issued: 12/16/2019 SDS No: AST CF-100 B Date Revised: 08/12/2020

Revision No: 2

American Safety Technologies CF-100 - Part B

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: American Safety Technologies CF-100 - Part B

MANUFACTURER

ITW Polymers Sealants North America 12055 Cutten Road Houston, TX 77066

Customer Service: (800) 878-7876

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

International: (703) 527-3887

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Oral), Category 4 Acute Toxicity (Dermal), Category 4 Acute Toxicity (Inhalation), Category 4 Skin Corrosion, Category 1 Serious Eye Damage, Category 1 Skin Sensitization, Category 1

Environmental:

Acute Hazards to the Aquatic Environment, Category 2 Chronic Hazards to the Aquatic Environment, Category 2

Physical:

Not classified

GHS LABEL





Corrosion

Exclamation Environment mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H332: Harmful if inhaled.

H411: Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P102: Keep out of reach of children.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray. 0694QGXV: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

Date Issued: 12/16/2019 SDS No: AST CF-100 B Date Revised: 08/12/2020

Revision No: 2

American Safety Technologies CF-100 - Part B

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER/doctor/...if you feel unwell.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P391: Collect spillage.

Storage:

P405: Store locked up.

Disposal:

5207XY7K: Dispose of contents/container according to local, regional, national, and international regulations.

HAZARDS NOT OTHERWISE CLASSIFIED: None known.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Benzyl Alcohol	30 - 60	100-51-6
3-aminomethyl-3,5,5-trimethylcyclohexylamine	10 - 30	2855-13-2
2-piperazin-1-ylethylamine	1 - 5	140-31-8
2,4,6-tris(dimethylaminomethyl)phenol	1 - 5	90-72-2

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

SKIN: Remove contaminated clothing. Wash the affected area immediately with large amounts of soap and water. Chemical burns must be treated by a physician. Get medical attention if irriations develops or persists. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash clothing before reuse.

INGESTION: Call a physician or poison control center immediately. Rinse mouth. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes severe eye damage - symptoms include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

SKIN: Burning pain and severe corrosive skin damage.

NOTES TO PHYSICIAN: Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Date Issued: 12/16/2019 SDS No: AST CF-100 B Date Revised: 08/12/2020

Revision No: 2

American Safety Technologies CF-100 - Part B

ADDITIONAL INFORMATION: If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this SDS to the doctor in attendance.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Class IIIB

GENERAL HAZARD: Combustible Liquid.

EXTINGUISHING MEDIA: Alcohol Resistant Foam, Powder, Carbon Dioxide (CO2)

OTHER CONSIDERATIONS: Do not use water jet as an extinguisher, as this will spread the fire.

FIRE FIGHTING PROCEDURES: Use standard firefighting procedures and consider the hazards of other involved materials.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do without risk. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.

FIRE FIGHTING EQUIPMENT: As in any fire, wear Self-Contained Breathing Apparatus (SCBA) MSHA/NIOSH approved or equivalent and full protective clothing.

FIRE EXPLOSION: No unusual fire or explosion hazards noted.

HAZARDOUS DECOMPOSITION PRODUCTS: During fire, gases hazardous to health may be formed

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the appropriate personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Know and prepare for spill response before using or handling this product. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled containers for disposal. Use appropriate PPE. Place absorbent diking materials in covered containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid run-off into storm drains, ditches and waterways.

RELEASE NOTES: Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

STORAGE: Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Date Issued: 12/16/2019 SDS No: AST CF-100 B Date Revised: 08/12/2020

Revision No: 2

American Safety Technologies CF-100 - Part B

EXPOSURE GUIDELINES

	EXPOS	LIDE LIMITS		
	EXPOSURE LIMITS			
Туре		ppm	mg/m³	
OSHA PEL	TWA	10 ppm	44.2 mg/m3	
OSHA PEL	TWA	NL [1]	NL ^[1]	
OSHA PEL	TWA	NL [1]	NL ^[1]	
OSHA PEL	TWA	NL [1]	NL ^[1]	
	STEL	NL [1]	NL ^[1]	
	TWA	NL [1]	NL [1]	
ACGIH TLV	STEL	NL [1]	NL ^[1]	
	OSHA PEL OSHA PEL	OSHA PEL TWA OSHA PEL TWA OSHA PEL TWA STEL ACGIH TLV	OSHA PEL TWA NL [1] OSHA PEL TWA NL [1] TWA NL [1] TWA NL [1] STEL NL [1] TWA NL [1]	

Footnotes:

1. NL = Not Listed

ENGINEERING CONTROLS: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields, goggles or full-face shield as required by 29 CFR 1910.133 - OSHA Eye and Face Protection Standard. A suitable emergency eye wash station and safety shower should be located near the work station

SKIN: Wear chemical resistant, impervious gloves.

RESPIRATORY: Where vapor concentrations exceed or are likely to exceed the occupational exposure limits, a NIOSH approved continuous flow supplied air respirator, hood or helmet is recommended. A NIOSH approved self-contained positive pressure breathing apparatus with full face piece is required for spills and/or emergencies.

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

PROTECTIVE CLOTHING: Chemical resistant gloves and normal work clothing (long sleeved shirt and long pants). Use of impervious apron is recommended.

WORK HYGIENIC PRACTICES: Use good hygiene practices when handling this material. Wash hands thoroughly after use before eating, drinking and/or smoking. When using do not smoke. Routinely was work clothing and protective equipment to remove contamination. Contaminated work clothing should not be allowed out of the workplace.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Slight
COLOR: Yellow
pH: Not Available

PERCENT VOLATILE: Not Available

FLASH POINT AND METHOD: > 93.3°C (200°F)

Date Issued: 12/16/2019 **SDS No**: AST CF-100 B **Date Revised**: 08/12/2020

Revision No: 2

American Safety Technologies CF-100 - Part B

FLAMMABLE LIMITS: Not Available to Not Available AUTOIGNITION TEMPERATURE: Not Available

VAPOR PRESSURE: < 1 mmHg VAPOR DENSITY: Not Available BOILING POINT: > 93.3°C (200°F) FREEZING POINT: Not Available MELTING POINT: Not Available

THERMAL DECOMPOSITION: Not Available SOLUBILITY IN WATER: Not Available

EVAPORATION RATE: < 1 (n-Butyl Acetate=1)

DENSITY: 8.67 lbs/gal SPECIFIC GRAVITY: 1.04 VISCOSITY: Not Available

(VOC): 0 gr/L

Notes: Mixed Components

10. STABILITY AND REACTIVITY

REACTIVITY: Product is stable and non-reactive under normal conditions of use, storage and transport

HAZARDOUS POLYMERIZATION: Product will not undergo polymerization.

STABILITY: Stable under normal storage and application conditions.

CONDITIONS TO AVOID: Avoid temperatues exceeding the flash point. Contact with incompatible materials.

POSSIBILITY OF HAZARDOUS REACTIONS: None

HAZARDOUS DECOMPOSITION PRODUCTS: No hazardous decomposition products are known.

INCOMPATIBLE MATERIALS: Peroxides. Phenols.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Benzyl Alcohol	1230 mg/kg	No data	No data
3-aminomethyl-3,5,5-trimethylcyclohexylamine	No data	No data	No data
2-piperazin-1-ylethylamine	2097 mg/kg (rats)	No data	No data
2,4,6-tris(dimethylaminomethyl)phenol	2169 mg/kg (rats)	No data	No data

NOTES: Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed.

SKIN CORROSION/IRRITATION: Causes severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction.

SERIOUS EYE DAMAGE/IRRITATION: Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION: Not a respiratory sensitizer. May cause an allergic skin reaction.

GERM CELL MUTAGENICITY: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic

CARCINOGENICITY

Date Issued: 12/16/2019 SDS No: AST CF-100 B Date Revised: 08/12/2020

Revision No: 2

American Safety Technologies CF-100 - Part B

IARC: Not listed.

NTP: Not listed.

OSHA: Not listed.

NOTES: Not classifiable as to carcinogenicity to humans.

REPRODUCTIVE TOXICITY: This product is not expected to cause reproductive or developmental effects.

STOT-SINGLE EXPOSURE: Not classified.

STOT-REPEATED EXPOSURE: Not classified.

ASPIRATION HAZARD: Not an aspiration hazard.

GENERAL COMMENTS: Chronic effects - Prolonged inhalation may be harmful.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Very toxic to aquatic life with long lasting effects. **BIOACCUMULATION/ACCUMULATION:** Partition coefficient n-octanol/water (log Kow)

Benzyl Alcohol - 1.1

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Consult with your state and local hazardous waste requirements or guidelines to ensure compliance. Arrange disposal in accordance with EPA, state and local requirements.

EMPTY CONTAINER: Since empties containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Paint

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: UN3066
PACKING GROUP: III
LABEL: Corrosive

OTHER SHIPPING INFORMATION: Read safety instructions, SDS and emergency procedures before handling

AIR (ICAO/IATA)

SHIPPING NAME: Paint UN/NA NUMBER: UN3066

PRIMARY HAZARD CLASS/DIVISION: 8

PACKING GROUP: III

ERG: 8L

LABEL: Corrosive

NOTE: Read safety instructions, SDS and emergency procedures before handling.

VESSEL (IMO/IMDG)

SHIPPING NAME: Paint, MARINE POLLUTANT

UN/NA NUMBER: UN3066

Date Issued: 12/16/2019 SDS No: AST CF-100 B Date Revised: 08/12/2020

Revision No: 2

American Safety Technologies CF-100 - Part B

PRIMARY HAZARD CLASS/DIVISION: 8

PACKING GROUP: III EmS: F-A, S-B

MARINE POLLUTANT #1: Yes

NOTE: Read safety instructions, SDS and emergency procedures before handling.

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION





Pollutant

IMDG Regulated Marine Pollutant

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: Not Regulated

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Benzyl Alcohol	100-51-6
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2
2-piperazin-1-ylethylamine	140-31-8
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2

CLEAN AIR ACT

40 CFR PART 68---RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION: Not Regulated

CLEAN AIR ACT (HAZARDOUS AIR POLLUTANTS): Not Regulated

STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
2,4,6-tris(dimethylaminomethyl)phenol	Massachusetts Right to Know List Pennsylvania Right to Know List New Jersey Right to Know List

OSHA HAZARD COMM. RULE: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SDWA (SAFE DRINKING WATER ACT): Not Regulated

16. OTHER INFORMATION

Date Revised: 08/12/2020


INFORMATION CONTACT: (800) 878-7876

Date Issued: 12/16/2019 **SDS No**: AST CF-100 B **Date Revised**: 08/12/2020

Revision No: 2

American Safety Technologies CF-100 - Part B

REVISION SUMMARY: This SDS replaces the 12/16/2019 SDS.





GENERAL STATEMENTS: Keep out of reach of children

For professional or industrial use only

MANUFACTURER DISCLAIMER: This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.