



## TECHNICAL DATA SHEET – LSA TRAX COAT

---

Revised:03/2023

### PRODUCT SPECIFICATION

Low Solar Absorbing LSA Acrylic copolymer one component anti-slip coating enhancer designed for application over non-skid deck coatings. Prevents loss of Coefficient of friction when coating over non-skids

**LSA Trax-Coat** can be used for use on flight decks for VLA, safety markings, center lines and aesthetic enhancement. The product has a non-reflective matte appearance and provides maximum adhesion, toughness, wears resistance and excels in exterior weatherability. The pigments contain special colors which minimize Intra-red absorption and minimize deck temperatures.

### SURFACE PREPARATION

LSA Trax-Coat can be applied to any clean, dry surface, free of loose materials. Remove oil, grease, dirt and other foreign matter by cleaning with a water-based cleaner/ degreaser or approved cleaning solvent, then thoroughly flush with water and allow to dry.

### MIXING AND APPLICATION

The container should be mixed thoroughly with an electric drill and a Jiffy® mixing blade for 3-5 minutes so that all material is uniform. The preferred method of application over non-skid is by a nap roller, but LSA Trax-Coat can also be readily applied by brush or spray. For most applications one coat is sufficient. If a second coat is needed apply the second coat over the first coat by about 24 hours.

### SURFACE MAINTENANCE

To maintain a clean surface we recommend periodic cleaning with an approved all purpose, biodegradable cleaner/ degreaser. Scrub surface with a long-handled, fiber bristled brush or floor machine, rinse with water and allow drying.

---

# LSA TRAX COAT

LOW ABSORBING WATER BASED  
ACRYLIC ANTI-SLIP ENHANCER

### PRODUCT SPECIFICATIONS

GENERIC DESCRIPTION	LSA Water Based Acrylic Anti-Slip Enhancer
V.O.C	1.7 lbs per gallon (211 grams/ liter)
SOLIDS BY WEIGHT	39.5%
WEIGHT PER GALLON	9.6 lbs per gallon
ESTIMATE COVERAGE	320 sq. ft./ gal@ 5 mils WFT
STANDARD COLOR	Dark Gray (36076)
SHELF LIFE	1 Year
FLASH POINT	None (Water Based)
PACKAGING	5 Gallon Kit

The responsibility for surface preparation and product application rests with the customer. Holcim Solutions and Products US LLC. will assume no liability or imply any warranty as to the serviceability of the products or application due to the fact we have no control over surface preparation, environmental conditions or application procedures. Holcim Solutions and Products US LLC. technical assistance is advisory only unless otherwise specified.

**CAUTION:** Read Safety Data Sheet before using this material. Use only with adequate cross ventilation. Keep away from extreme heat, sparks and open flame. Keep from freezing. Avoid prolonged breathing of vapors. For dizziness, seek fresh air. Avoid contact with skin. Use gloves, goggles and coveralls. In case of spillage on clothing, change clothing to prevent prolonged contact with skin. Wash contaminated clothing before reuse. In case of accidental contact with skin, wash immediately with soap and water. In case of eye contact, flush thoroughly with plenty of water and call physician. If swallowed accidentally, do not induce vomiting. Seek medical attention immediately. The user of this product is responsible for making its own evaluation and tests regarding the capabilities, safety, utility, suitability and application of the product, and assumes all risks and liabilities resulting from the use or application of the product, whether used alone or with other products. EXCLUSION OF WARRANTIES: INSTALL AS DIRECTED ON AMERICAN SAFETY TECHNOLOGIES PRODUCT DATA SHEET. USER DETERMINES SUITABILITY FOR INTENDED USE AND ASSUMES ALL RISK AND LIABILITY. THIS PRODUCT IS SOLD "AS IS". EXCEPT AS REQUIRED BY LAW, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IF TERMS ARE NOT ACCEPTABLE, RETURN UNOPENED PRODUCT TO PLACE OF PURCHASE.