

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 05/10/2022

Revision date: 10/03/2023

Supersedes: 03/23/2023

Version: 3.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Coating

1.3. Supplier

Holcim Solutions and Products US, LLC
26 Century Boulevard, Suite 205
Nashville, Tennessee 37214
1-800-878-7876 • www.holcimast.com

Manufactured at: 12055 Cutten Road, Houston TX 77066

1.4. Emergency telephone number

Emergency number : CHEMTREC (US Transportation): (800) 424-9300 International: +1 (703) 527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/irritation, Category 2A	H319
Skin sensitization, Category 1	H317
Carcinogenicity, Category 2	H351
Hazardous to the aquatic environment - Chronic Hazard, Category 2	H411

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

H226 - Flammable liquid and vapor
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H351 - Suspected of causing cancer
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, chemical goggles, & face protection.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P391 - Collect spillage.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer	(CAS-No.) 25085-99-8	10 – 30
Trizinc diphosphate	(CAS-No.) 7779-90-0	5 – 10
Xylene	(CAS-No.) 1330-20-7	1 – 5
Bisphenol A diglycidyl ether - bisphenol A copolymer	(CAS-No.) 25036-25-3	1 – 5
Propylene glycol monomethyl ether	(CAS-No.) 107-98-2	1 – 5
Bisphenol A-epichlorohydrin polymer	(CAS-No.) 25068-38-6	1 – 5
Oxirane, 2,2'-[oxybis[(methyl-2,1-ethanediyl)oxymethylene]]bis-	(CAS-No.) 41638-13-5	1 – 5
Trimethylolpropane triacrylate	(CAS-No.) 15625-89-5	1 – 5
Ethylbenzene	(CAS-No.) 100-41-4	0.1 – 1

* In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
First-aid measures after skin contact	: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention immediately.
First-aid measures after eye contact	: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: Suspected of causing cancer.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Carbon dioxide. Dry powder.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.

Explosion hazard : Product is not explosive.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire : Eliminate all ignition sources if safe to do so.

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment/cleaning up : SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

6.4. Reference to other sections

See Sections 8 and 13.

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : For professional or industrial use only. Follow label instructions. Keep out of reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Keep container closed when not in use. Containers which are opened should be properly resealed and kept upright to prevent leakage. Store in a dry, cool and well-ventilated place.

Incompatible materials : No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethylbenzene (100-41-4)		
ACGIH	ACGIH OEL TWA [ppm]	20 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; ototoxicity; kidney eff; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2022
OSHA	OSHA PEL (TWA) [1]	435 mg/m³
OSHA	OSHA PEL (TWA) [2]	100 ppm
OSHA	OSHA PEL (STEL) [1]	545 mg/m³
OSHA	OSHA PEL (STEL) [2]	125 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH [ppm]	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA)	435 mg/m³
NIOSH	NIOSH REL TWA [ppm]	100 ppm
NIOSH	NIOSH REL (STEL)	545 mg/m³
NIOSH	NIOSH REL STEL [ppm]	125 ppm
Bisphenol A diglycidyl ether - bisphenol A copolymer (25036-25-3)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Propylene glycol monomethyl ether (107-98-2)		
ACGIH	ACGIH OEL TWA [ppm]	100 ppm
ACGIH	ACGIH OEL STEL [ppm]	150 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2022
OSHA	OSHA PEL (TWA) [1]	360 mg/m³
OSHA	OSHA PEL (TWA) [2]	100 ppm
OSHA	OSHA PEL (STEL) [1]	540 mg/m³

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propylene glycol monomethyl ether (107-98-2)		
OSHA	OSHA PEL (STEL) [2]	150 ppm
NIOSH	NIOSH REL (TWA)	360 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	100 ppm
NIOSH	NIOSH REL (STEL)	540 mg/m ³
NIOSH	NIOSH REL STEL [ppm]	150 ppm
Bisphenol A-epichlorohydrin polymer (25068-38-6)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Oxirane, 2,2'-[oxybis[(methyl-2,1-ethanediyl)oxymethylene]]bis- (41638-13-5)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer (25085-99-8)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Trimethylolpropane triacrylate (15625-89-5)		
OSHA	Remark (OSHA)	OELs not established
AIHA	WEEL TWA	1 mg/m ³
Trizinc diphosphate (7779-90-0)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Xylene (1330-20-7)		
ACGIH	ACGIH OEL TWA	221 mg/m ³
ACGIH	ACGIH OEL TWA [ppm]	50 ppm
ACGIH	ACGIH OEL STEL	442 mg/m ³
ACGIH	ACGIH OEL STEL [ppm]	100 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; hematologic eff; ototoxicity (for mixtures containing p-xylene); CNS impair. Notations: OTO (for mixtures containing p-xylene); A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2022
OSHA	OSHA PEL (TWA) [1]	435 mg/m ³
OSHA	OSHA PEL (TWA) [2]	100 ppm
OSHA	OSHA PEL (STEL) [1]	655 mg/m ³
OSHA	OSHA PEL (STEL) [2]	150 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ensure adequate ventilation, especially in confined areas.

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Protective clothing.

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Be aware that the chemical may penetrate the gloves. Frequent changes are advisable. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection:

Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment. An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Dark Gray; Buff; Haze Gray
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: >38.9 °C (102.2 °F)
Relative evaporation rate (n-butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Static electricity. Heat. Sparks. Open flame.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Ethylbenzene (100-41-4)

LD50 oral rat 3500 mg/kg

LD50 dermal rabbit 15400 mg/kg

LC50 Inhalation - Rat 17.2 mg/l/4h

LC50 Inhalation - Rat [ppm] 4000 ppm Source: ECHA, Harmonized classification of EU CLP

Bisphenol A diglycidyl ether - bisphenol A copolymer (25036-25-3)

LD50 oral rat > 2000 mg/kg

LD50 dermal rabbit > 2000 mg/kg

Propylene glycol monomethyl ether (107-98-2)

LD50 oral rat 5200 mg/kg

LD50 dermal rat > 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))

LD50 dermal rabbit 13000 mg/kg

LC50 Inhalation - Rat 54.6 mg/l/4h

LC50 Inhalation - Rat [ppm] > 7559 ppm (Exposure time: 6 h)

Bisphenol A-epichlorohydrin polymer (25068-38-6)

LD50 oral rat 11400 mg/kg

LD50 dermal rat > 2000 mg/kg Source: CHEMIDPLUS

Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer (25085-99-8)

LD50 oral rat > 4000 mg/kg

LD50 dermal rabbit > 20000 mg/kg

Trimethylolpropane triacrylate (15625-89-5)

LD50 oral rat 5190 mg/kg

LD50 dermal rabbit 5000 mg/kg

Trizinc diphosphate (7779-90-0)

LD50 oral rat > 5000 mg/kg

LC50 Inhalation - Rat > 5700 mg/m³ Source: ECHA

Xylene (1330-20-7)

LD50 oral rat 3500 mg/kg

LD50 dermal rabbit 12126 mg/kg body weight Animal: rabbit, Animal sex: male, Remarks on results: other:

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylene (1330-20-7)	
LC50 Inhalation - Rat [ppm]	5922 ppm

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not applicable
Symptoms/effects	: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation.
Chronic symptoms	: Suspected of causing cancer.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: No data available.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects	: No data available.
-----------------------	----------------------

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

DOT Non-Bulk (NOTE: Non-bulk packaging means a packaging which has: (1) A maximum capacity of 450 L (119 gallons) or less as a receptacle for a liquid)

Not regulated as dangerous goods.

Non-bulk: Not hazardous for transport under 49 CFR exceptions 173.150 (f) (1, 2, 3).

DOT Bulk

Transport document description (DOT)	: UN1263 Paint, 3, III
UN-No.(DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 3 - Flammable liquid



Dangerous for the environment	: Yes
Marine pollutant	: Yes

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
--	--------

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
--	---------

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
-----------------------------	---

Emergency Response Guide (ERG) Number	: 128
---------------------------------------	-------

Other information	: No supplementary information available.
-------------------	---

Transport by sea (IMDG)

Transport document description (IMDG)	: UN 1263 PAINT, 3, III
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L
Marine pollutant	: Yes

Air transport (IATA)

Transport document description (IATA)	: UN 1263 Paint, 3, III
UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information


15.1. US Federal regulations

MS-8CZ - Part A	
All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Skin corrosion or Irritation Health hazard - Carcinogenicity Health hazard - Serious eye damage or eye irritation
Ethylbenzene (100-41-4)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
Xylene (1330-20-7)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb

15.2. International regulations

Naphthalene (91-20-3)	
Toxic Substance (CEPA – Schedule I)	Yes

15.3. US State regulations

 **WARNING:** This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Ethylbenzene (100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	
Trimethylolpropane triacrylate (15625-89-5)	X					
Toluene (108-88-3)		X				7000 µg/day
Benzene (71-43-2)	X	X	X		6.4 µg/day (oral); 13 µg/day (inhalation)	24 µg/day (oral); 49 µg/day (inhalation)
Cumene (98-82-8)	X					
Carbon black (1333-86-4)	X					
Titanium dioxide (13463-67-7)	X				Not available	
Naphthalene (91-20-3)	X				5.8 µg/day	
Arsenic (7440-38-2)	X	X			0.06 µg/day (inhalation) 10 µg/day (except inhalation)	
Aniline (62-53-3)	X				100 µg/day	

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Ethylbenzene (100-41-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Propylene glycol monomethyl ether (107-98-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Xylene (1330-20-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
n-Butyl acetate (123-86-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List
Toluene (108-88-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Benzene (71-43-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Phosphoric acid (7664-38-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Cumene (98-82-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Titanium dioxide (13463-67-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Lead (7439-92-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) List
Cadmium (non-pyrophoric) (7440-43-9)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Carbon black (1333-86-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Nickel (7440-02-0)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Arsenic (7440-38-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Naphthalene (91-20-3)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Benzene, 1,2,4-trimethyl- (95-63-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Diisobutyl ketone (108-83-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List
Barium sulfate (7727-43-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
1,3,5-Trimethylbenzene (108-67-8)	U.S. - Massachusetts - Right To Know List
Benzene, trimethyl- (25551-13-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List
Talc (14807-96-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Carbonic acid, magnesium salt (1:1) (546-93-0)	U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List

MS-8CZ Part A Dark Gray; MS-8CZ Part A Buff; MS-8CZ Part A Haze Gray

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Benzene, ethylmethyl- (25550-14-5)	U.S. - New Jersey - Right to Know Hazardous Substance List
n-Propylbenzene (103-65-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Methyl n-amyl ketone (110-43-0)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List
Aniline (62-53-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information


Other information : Author: JAD.

Revision date : 10/03/2023

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



HMIS Hazard Rating

Health : 2

* - Chronic (long-term) health effects may result from repeated overexposure

Flammability : 2

Physical : 0

Indication of changes:

Revision 1.0: New SDS Created.

Revision 2.0: Updated supplier.

Revision 3.0: Updated transport information.

EXCLUSION OF WARRANTIES: INSTALL AS DIRECTED ON AMERICAN SAFETY TECHNOLOGIES PRODUCT DATA SHEET. USER DETERMINES SUITABILITY FOR INTENDED USE AND ASSUMES ALL RISK AND LIABILITY. THIS PRODUCT IS SOLD "AS IS". EXCEPT AS REQUIRED BY LAW, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IF TERMS ARE NOT ACCEPTABLE, RETURN UNOPENED PRODUCT TO PLACE OF PURCHASE.

American Safety Technologies® is a Holcim Solutions and Products US, LLC brand