

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 03/31/2022 Revision date: 03/22/2023 Version: 2.0

SECTION 1	1: Identification	
------------------	-------------------	--

 Identification

 Product form
 : Mixture

 Product name
 : MS-4100 Part A

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Holcim Solutions and Products US, LLC 26 Century Boulevard, Suite 205 Nashville, Tennessee 37214 1-800-878-7876 • www.holcimast.com

Manufactured at: 12055 Cutten Road, Houston TX 77066

1.4. Emergency telephone number

Emergency number

: CHEMTREC (US Transportation): (800) 424-9300 International: +1 (703) 527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 2	H315
Serious eye damage/irritation, Category 2	H319
Skin sensitization, Category 1	H317
Hazardous to the aquatic environment - Acute Hazard, Category 2	H401
Hazardous to the aquatic environment - Chronic Hazard, Category 2	H411

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard	pictograms	GHS US	۱
Tiazaiu	DICIOULATINS		,

Signal word (GHS US)	: Warning
Hazard statements (GHS US)	: H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H401 - Toxic to aquatic life H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (GHS US)	 P261 - Avoid breathing mist/vapors/spray. P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing must not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, chemical goggles, & face protection. P302+P352 - If on skin: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P363 - Wash contaminated clothing before reuse. P391 - Collect spillage. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
2,5,8,10-Tetraoxatridec-12-enoic acid, 9-oxo-, 2-propenyl ester, homopolymer	(CAS-No.) 25656-90-0	10 – 30
Cyclohexanol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane	(CAS-No.) 30583-72-3	10 – 30
Glass, oxide	(CAS-No.) 65997-17-3	5 – 10
Bisphenol A-epichlorohydrin polymer	(CAS-No.) 25068-38-6	1 – 5
Oxirane, 2,2'-[oxybis[(methyl-2,1-ethanediyl)oxymethylene]]bis-	(CAS-No.) 41638-13-5	1 – 5
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS-No.) 41556-26-7	0.1 – 1
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	(CAS-No.) 82919-37-7	0.1 – 1
Alkyl (C12-14) glycidyl ether	(CAS-No.) 68609-97-2	0.1 – 1

*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret

SECTION 4: First-aid measures				
4.1. Description of first aid measures				
First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.				
First-aid measures after inhalation	 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration. 			
First-aid measures after skin contact	: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention immediately.			
First-aid measures after eye contact	: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.			
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.			
4.2. Most important symptoms and effects (acute and delayed)				
Symptoms/effects	: Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction.			
Symptoms/effects after inhalation	: May cause minor respiratory irritation.			
Symptoms/effects after skin contact : Causes skin irritation. May cause an allergic skin reaction.				
Symptoms/effects after eye contact	: Causes serious eye irritation.			

Symptoms/effects after ingestion : May cause gastrointestinal irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguis	Suitable (and unsuitable) extinguishing media	
Suitable extinguishing media	: Foam. Carbon dioxide. Dry powder.	
5.2. Specific hazards arising from the c	hemical	
Fire hazard	: Not flammable.	
Explosion hazard	: Product is not explosive.	
Reactivity	: No dangerous reactions known under normal conditions of use.	
5.3. Special protective equipment and precautions for fire-fighters		
Precautionary measures fire	: Eliminate all ignition sources if safe to do so.	
Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Do not dispose of fire-fighting water in the environment.	
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1 Personal pressutions prot	ECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eve protection.			
6.1.1. For non-emergency person	nel		
Protective equipment	: Wear protective equipment as described in section 8.		
Emergency procedures	: Evacuate unnecessary personnel.		
6.1.2. For emergency responders			
Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.		
6.2. Environmental precautions			
Avoid release to the environment. Prev	ent entry to sewers and public waters.		
6.3. Methods and material for c	ontainment and cleaning up		
For containment/cleaning up	: SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.		
	LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.		

See Sections 8 and 13.

SECTION 7: Handling and storage		
7.1.	Precautions for safe handling	
Precautions for safe handling		: For professional or industrial use only. Follow label instructions. Keep out of reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.
7.2.	Conditions for safe storage, including any incompatibilities	
Storage	e conditions	Store in original container. Keep container closed when not in use. Containers which are opened should be properly resealed and kept upright to prevent leakage. Store in a dry, cool and well-ventilated place.
Incomp	atible materials	: No data available.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

-		
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
2,5,8,10-Tetraoxa	tridec-12-enoic acid, 9-oxo-, 2-pro	penyl ester, homopolymer (25656-90-0)
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Bisphenol A-epic	hlorohydrin polymer (25068-38-6)	
ACGIH	Remark (OSHA)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Cyclohexanol, 4,4	4'-(1-methylethylidene)bis-, polym	er with (chloromethyl)oxirane (30583-72-3)
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Oxirane, 2,2'-[oxy	/bis[(methyl-2,1-ethanediyl)oxyme	thylene]]bis- (41638-13-5)
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Alkyl (C12-14) gly	/cidyl ether (68609-97-2)	
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Glass, oxide (659	97-17-3)	
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established

8.2. Appropriate engineering controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ensure adequate ventilation, especially in confined areas.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Wear chemically impervious apron over labcoat and full coverage clothing.

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Be aware that the chemical may penetrate the gloves. Frequent changes are advisable. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection:

Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment. An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and	chemical properties	
Physical state	: Liquid	
Color	: Gray	
Odor	: Slight	
Odor threshold	: No data available	
рН	: No data available	
Melting point	: No data available	
Freezing point	: No data available	
Boiling point	: No data available	
Flash point	: > 201 °F (>93.9 °C)	
Relative evaporation rate (n-butyl acetate=1)	: No data available	
Flammability (solid, gas)	: No data available	
Vapor pressure	: 0.03 mm Hg	
Relative vapor density at 20 °C	: No data available	
Relative density	: No data available	
Density	: 1.75 g/cm³	

Explosion limits	
Explosive properties	
Oxidizing properties	

Partition coefficient n-octanol/water (Log Pow)

9.2. Other information

Auto-ignition temperature

Viscosity, dynamic

VOC content

Decomposition temperature Viscosity, kinematic

: 22 g/l mixed components

: 1.75

: No data available

: No data available

No data availableNo data available

: No data available

No data availableNo data availableNo data available

: Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Specific gravity

Solubility

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources. Avoid static charge accumulation and discharge. . Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological informati	on	
11.1. Information on toxicologica	l effects	
Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)	
LD50 oral rat	2615 mg/kg	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ccording to Federal Register / Vol. 77, No. 58 / Monday			
Bisphenol A-epichlorohydrin polymer (25068	· ·		
LD50 oral rat	11400 mg/kg		
LD50 dermal rat	> 2000 mg/kg Source: CHEMIDPLUS		
Cyclohexanol, 4,4'-(1-methylethylidene)bis-,	polymer with (chloromethyl)oxirane (30583-72-3)		
LD50 oral rat	2000 mg/kg Source: ECHA		
LD50 dermal rat	> 2000 mg/kg		
Alkyl (C12-14) glycidyl ether (68609-97-2)			
LD50 oral rat	17100 mg/kg		
LD50 dermal rabbit	> 3987 mg/kg		
Glass, oxide (65997-17-3)			
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)		
Skin corrosion/irritation	: Causes skin irritation.		
Serious eye damage/irritation	: Causes serious eye irritation.		
Respiratory or skin sensitization	: May cause an allergic skin reaction.		
Germ cell mutagenicity	: Not classified		
Carcinogenicity	: Not classified		
Reproductive toxicity	: Not classified		
STOT-single exposure	: Not classified		
STOT-repeated exposure	: Not classified		
Aspiration hazard	: Not classified		
∕iscosity, kinematic	: Not applicable		
Symptoms/effects	: Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction.		
Symptoms/effects after inhalation	: May cause minor respiratory irritation.		
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.		
Symptoms/effects after eye contact	: Causes serious eye irritation.		
Symptoms/effects after ingestion	: May cause gastrointestinal irritation.		
SECTION 12: Ecological information			
12.1. Toxicity			
Ecology - general	: No data available.		
Hazardous to the aquatic environment, short- term (acute)	: Toxic to aquatic life.		
Hazardous to the aquatic environment, long- term (chronic)	: Toxic to aquatic life with long lasting effects.		
12.2. Persistence and degradability			
No additional information available			
12.3. Bioaccumulative potential			
No additional information available			
12.4. Mobility in soil			
No additional information available			
12.5. Other adverse effects			
Other adverse effects	: No data available.		
SECTION 13: Disposal considerations			
13.1. Disposal methods			
Waste treatment methods	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.		
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

Department of Transportation (DOT)	
In accordance with DOT	
Transport document description (DOT)	: UN3082 Environmentally hazardous substances, liquid, n.o.s. (contains Bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate ; Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4- piperidinyl ester), 9, III
UN-No.(DOT)	: UN3082
Proper Shipping Name (DOT)	: Environmentally hazardous substances, liquid, n.o.s.
Class (DOT)	: 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 9 - Class 9 (Miscellaneous dangerous materials)
Dangerous for the environment	: Yes
Marine pollutant	: Yes
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 171
Other information	: No supplementary information available.
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No limit
Transport by sea (IMDG)	
Transport document description (IMDG)	: UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis(1,2,2,6,6- pentamethyl-4-piperidyl) sebacate ; Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4- piperidinyl ester), 9, III
UN-No. (IMDG)	: 3082
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class (IMDG)	: 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5L
Marine pollutant	: Yes
	× ×
Air transport (IATA)	
	LINE 2020 Environmentally because whether a limit of a set (Dis (4.0.0.0.0) mentals that 4

Transport document description (IATA)

UN-No. (IATA) Proper Shipping Name (IATA) Class (IATA) Packing group (IATA)

- : UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate ; Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester), 9, III : 3082
- : Environmentally hazardous substance, liquid, n.o.s.
- : 9 Miscellaneous Dangerous Substances and Articles
- : III Minor Danger

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

MS-4100 Part A

All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA SARA Section 311/312 Hazard Classes Health hazard - Skin corrosion or Irritation

SARA Section 311/312 Hazard Classes	Health hazard - Skin corrosion or Irritation
	Health hazard - Serious eye damage or eye irritation
	Health hazard - Respiratory or skin sensitization

15.2. International regulations

Epichlorohydrin (106-89-8)	
Toxic Substance (CEPA – Schedule I)	Yes
Naphthalene (91-20-3)	
Toxic Substance (CEPA – Schedule I)	Yes

15.3. US State regulations

WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)	
Ethylbenzene (100-41- 4)	Х				54 μg/day (inhalation); 41 μg/day (oral)		
Toluene (108-88-3)		X				7000 µg/day	
Benzene (71-43-2)	Х	X	X		6.4 μg/day (oral); 13 μg/day (inhalation)	24 μg/day (oral); 49 μg/day (inhalation)	
Cumene (98-82-8)	x						
Methyl chloride (74- 87-3)		X	x				
Silica: Crystalline, quartz (14808-60-7)	Х						
Titanium dioxide (13463-67-7)	Х				Not available		
Epichlorohydrin (106- 89-8)	Х		x		9 µg/day		
Naphthalene (91-20-3)	Х				5.8 µg/day		
Palygorskite (12174- 11-7)	Х						
Component		State or I	ocal regulations				
Xylene (1330-20-7)			U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List				
Benzene (71-43-2)			U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List				
n-Butyl acetate (123-86-	4)	Hazardou	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List		w) -		
Toluene (108-88-3)			U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List				

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations			
Ethylbenzene (100-41-4)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List			
Isobutyl alcohol (78-83-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List			
Titanium dioxide (13463-67-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania RTK (Right to Know) List; U.S Massachusetts - Right To Know List			
Isopropyl alcohol (67-63-0)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List			
Cumene (98-82-8)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances			
Naphthalene (91-20-3)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List			
Benzene, 1,2,4-trimethyl- (95-63-6)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List			
Silica: Crystalline, quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania RTK (Right to Know) List; U.S Massachusetts - Right To Know List			
Barium sulfate (7727-43-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania RTK (Right to Know) List			
Benzene, trimethyl- (25551-13-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusett - Right To Know List; U.S Pennsylvania - RTK (Right to Know) List			
Magnesium oxide (1309-48-4)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List			
Epichlorohydrin (106-89-8)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List			
Benzene, ethylmethyl- (25550-14-5)	U.S New Jersey - Right to Know Hazardous Substance List			
n-Propylbenzene (103-65-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List			
Methyl chloride (74-87-3)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List			
Methyl n-amyl ketone (110-43-0)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) List			
Diatomaceous Earth, Natural (61790-53-2)	U.S New Jersey - Right to Know Hazardous Substance List			

SECTION 16: Other information

Other information Revision date

: Author: JAD.

: 03/22/2023

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
HMIS Hazard Rating	·
Health	: 2
Flammability	: 1
Physical	: 0
Indication of changes: Revision 1.0: New SDS Created. Revision 2.0. Updated supplier.	

EXCLUSION OF WARRANTIES: INSTALL AS DIRECTED ON AMERICAN SAFETY TECHNOLOGIES PRODUCT DATA SHEET. USER DETERMINES SUITABILITY FOR INTENDED USE AND ASSUMES ALL RISK AND LIABILITY. THIS PRODUCT IS SOLD "AS IS". EXCEPT AS REQUIRED BY LAW, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IF TERMS ARE NOT ACCEPTABLE, RETURN UNOPENED PRODUCT TO PLACE OF PURCHASE.

American Safety Technologies® is a Holcim Solutions and Products US, LLC brand