



VOC DATA SHEET

PROPERTIES OF THE MARINE COATING OR THINNER "AS SUPPLIED" BY THE MANUFACTURER

Manufacturer: ITW POLYMERS SEALANTS NORTH AMERICA
Product Identification: MS-200 Colors: Dark Gray, Green, Red, Yellow

MACT Coating Category: General Use \_\_\_\_\_ or Specialty Coating \_\_\_X\_\_\_
If coating is a Specialty Coating, please list the specific Category type(s) below...
Semi Gloss and Special Marking

Is this product a coating or thinner? COATING \_\_\_X\_\_\_ THINNER \_\_\_\_\_

If product is a coating or paint, please provide the information requested in Items A through J below:

If the product is thinner or reducer, please provide the information requested in Items D through J below:

Properties of the coating or thinner as supplied to the customer:

- A. Coating Density: (Dc) 1138 ± 2 g/L or 9.5 ± 0.2 lbs/gal [ ] ASTM D1475-90 [X] Other
B. Total Volatiles: (Mv) 34 ± 0.2 Mass Percent [ ] ASTM D2369-93 [X] Other
C. Cure Volatiles Content: (Ccv) 0 g/L or 0 lbs/gal [ ] Calculated [ ] Other
D. Organic Volatiles: (Mo) 34 ± 0.2 Mass Percent [ ] Calculated [ ] Other
E. Water Content
1 (Mw) 0 Mass Percent [ ] ASTM D3792-91 [ ] ASTM D4017-90 [ ] Other
2 (Vw) 0 Volume Percent [ ] Calculated [ ] Other
F. Exempt Compounds Content: (Cex) 0 g/L or 0 lbs/gal [ ] Calculated [ ] Other
G. Non-volatiles: (Vs) 56 ± 2% Volume Percent [X] Calculated [ ] Other
H. VOC Content (VOC)
1 383 ± 6 g/L or 3.2 ± 0.05 lbs/gal solids (non-volatiles)
2 383 ± 6 g/L or 3.2 ± 0.05 lbs/gal coatings (less water and exempt compounds)
I. Thinner Density: (Dth) N/A g/L or N/A lbs/gal [ ] ASTM [X] Other